



Product Bulletin



Follow us on Twitter @mountztorque

PB # 0056 November 2014

www.mountztorque.com

IPT

Click Wrench (Preset)



- Designed and manufactured to meet or exceed the accuracy and repeatability of ISO 6789:2003 (+/- 4% of setting).
- Durable and robust for industrial fastening applications.
- Preset torque wrench with a square drive. Bi-directional ratchet head.
- Tamper-proof internal adjustment. No external adjustment scale - must be preset using a torque analyzer. Requires Torque Adjusting Key* (sold separately)
- Crafted with strong steel shaft with high corrosion resistance.
- Lightly knurled non-slip grip.
- 48 tooth ratchet.
- Positive "click" can be heard and felt when torque is reached.

| Model | Item # | Torque Ranges | | | Length | | Weight | |
|---------|--------|----------------------|----------------|--------------|---------|------|--------|------|
| | | American | S.I. | Square Drive | in | mm | lbs. | kg. |
| IPT 18 | 280041 | 3.7 - 18.4 lbf.ft | 5 -25 N.m | 1/4" | 8 7/8" | 226 | 0.7 | 0.32 |
| IPT 36 | 280042 | 7.4 - 36.9 lbf.ft | 10 - 50 N.m | 3/8" | 11 7/8" | 300 | 1.4 | 0.62 |
| IPT 73 | 280043 | 14.8 - 73.8 lbf.ft | 20 - 100 N.m | 3/8" | 14 3/4" | 376 | 1.8 | 0.8 |
| IPT 110 | 280044 | 22.1 - 110.7 lbf.ft | 30 - 150 N.m | 3/8" | 15 1/4" | 386 | 2.4 | 1.08 |
| IPT 150 | 280045 | 29.5 - 147.6 lbf.ft | 40 - 200 N.m | 1/2" | 19 2/3" | 500 | 2.9 | 1.33 |
| IPT 250 | 280046 | 44.3 - 250.9 lbf.ft | 60 - 340 N.m | 1/2" | 23 1/8" | 587 | 3.9 | 1.78 |
| IPT 369 | 280047 | 73.8 - 369 lbf.ft | 100 - 500 N.m | 3/4" | 34" | 865 | 12.1 | 5.5 |
| IPT 885 | 280048 | 171.1 - 885.6 lbf.ft | 240 - 1200 N.m | 1" | 58 1/4" | 1480 | 13 | 5.9 |



* Note - The **IPT Torque Adjusting Set Key** is required to adjust the internal torque setting for models: IPT 18 - IPT 250 models. (A 3mm Allen Key is needed to adjust the internal torque setting for models: IPT 369 - IPT 885 models)

Item # 280049
Model: IPT Torque Adjusting Set Key